



Directive 2002/95/EC  
"RoHS"  
Compliant

NOTES:

1. METALSHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
2. INSULATORS: PBT GF UL 94 V-0, GREEN
3. SIGNAL CONTACTS: COPPER ALLOY  
PLATING: 30µin HARD GOLD over min. 50µin NICKEL  
SOLDER CUP ACCEPTS CABLE AWG 20
4. NO CONTACTS ON POS A1 and A2
5. THREADED INSERT: COPPER ALLOY; min. 200µin TIN over 80µin NICKEL
6. COLLAR: COPPER ALLOY; min. 200µin TIN over 80µin NICKEL
7. MAXIMUM TORQUE VALUE FOR THREAD: 6 in.LB
8. CONNECTOR IS PART MARKED: 3017W2SCM99A30X CONEC ABC

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	
CUSTOMER APPROVAL DATE:	
NAME:	TITLE:
COMPANY NAME:	
APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH				tolerance		dim. in mm	scale:	
				ISO 2768-m			2:1 (5:1)	
DO NOT ALTER CAD DRAWING BY HAND				date	name		title: <b>D-SUB COMBINATION FEMALE</b> 17W2S SOLDER CUP with threaded insert	
				drawn	06.12.01	Parei		
appd.	06.12.01	Mickenbecker						
norm								
d-old				dwg no:		Inventor 10	DIN-A3	
a	Origin			13K1A427A		sh: 1		
rev.	description	date	name	<b>CONEC</b>		part no: 3017W2SCM99A30X		

material:		see notes	
title: <b>D-SUB COMBINATION FEMALE</b> 17W2S SOLDER CUP with threaded insert			
dwg no:		Inventor 10	DIN-A3
		sh: 1	
part no:		3017W2SCM99A30X	